

HS36 ジブクレーン定格荷重表

作業半径 (m)	15mジブ		18mジブ		21mジブ		24mジブ		28mジブ	
	ジブ角度 (度)	定格荷重 (t)	ジブ角度 (度)	定格荷重 (t)	ジブ角度 (度)	定格荷重 (t)	ジブ角度 (度)	定格荷重 (t)	ジブ角度 (度)	定格荷重 (t)
3.4	79.8	2.8								
3.9	77.8	2.8	79.8	2.8						
4.4	75.8	2.8	78.2	2.8	79.9	2.8				
4.9	73.8	2.8	76.6	2.8	78.5	2.8	80.0	2.8		
5.4	72.2	2.8	75.3	2.8	77.2	2.8	78.8	2.8	80.0	2.8
5.9	69.5	2.8	73.0	2.8	75.5	2.8	77.4	2.8	78.2	2.8
6	69.4	2.8	72.9	2.8	75.4	2.8	77.3	2.8	78.1	2.8
7	65.2	2.8	69.6	2.8	72.6	2.8	74.8	2.8	76.3	2.8
8	61.0	2.8	66.1	2.8	69.7	2.8	72.3	2.8	75.2	2.8
9	56.5	2.8	62.6	2.8	66.8	2.8	69.8	2.8	72.8	2.8
10	51.8	2.8	59.0	2.8	63.8	2.8	67.3	2.8	70.0	2.8
11	46.7	2.8	55.2	2.8	60.7	2.8	64.6	2.8	65.3	2.8
12	41.2	2.8	51.2	2.8	57.5	2.8	62.0	2.8	63.5	2.64
12.8	36.4	2.8	47.8	2.8	54.9	2.8	59.8	2.58	62.1	2.52
13	35.0	2.76	47.0	2.76	54.2	2.76	59.2	2.54	62.0	2.31
14	27.7	2.57	42.5	2.57	50.8	2.57	56.4	2.35	59.2	2.12
15	17.8	2.40	37.5	2.40	47.2	2.40	53.5	2.18	58.1	1.97
16			31.9	2.25	43.3	2.25	50.5	2.04	55.4	1.83
17			25.3	2.11	39.2	2.11	47.3	1.92	51.8	1.72
18			16.3	2.00	34.6	2.00	43.9	1.80	48.0	1.61
19					29.5	1.89	40.4	1.70	46.1	1.50
20					23.4	1.80	36.8	1.60	44.9	1.39
21					15.0	1.71	32.3	1.52	38.7	1.29
22							27.5	1.44	36.8	1.19
23							21.8	1.36	31.7	1.10
23.9							15.0	1.30	28.6	1.02
24									26.2	0.94
25									20.2	0.87
26									17.6	0.80
26.9									15.0	0.74
27										
28										
29										
29.9										

フック重量:51kg